

Standard Printer **TDP225**



TDP-225 direct thermal printer features a compact design and high performance engine that make it ideal for retail and other labeling applications.

The TDP-225 prints at 5 ips and is the first low-cost compact 2-inch desktop printer to offer an optional LCD display for easy tracking of print job status. Other outstanding features include an inexpensive internal Ethernet adapter for easy integration into networks and an optional keyboard for printing labels in stand-alone or down-time situations.

Designed with no losable parts, the compact TDP-225 fits into tight spaces and supports a wide range of applications. It also features a user-friendly clamshell design that allows users to simply open the cover and drop labels into a spring-loaded 5-inch OD media bay.

TECHNICAL SPECIFICATIONS

| Technology | Direct thermal |
|------------------------|---|
| Print Head Type | Flat |
| Resolution | 203 dpi |
| Print Width | 54 mm (2.13") |
| Print Length | Max. 2286 mm (90*) |
| Print Speed | 127 mm (5")/second |
| Interface | RS-232, USB 2.0. |
| Barcodes | Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN- |
| | 13, EAN-128, UPC-A, UPC-E, EAN ir UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, China POST, |
| | GS1 Data Bar, Code 11. |
| 2D Codes | PDF-417, Maxicode, DataMatrix, QR code, Aztec. |
| Optional | Peel-off module, Guillotine cutter (full cut or partial cut), Internal Ethernet 10/100 Mbps, External |
| | 802.11 b/g/n wireless, 128 x 64 pixels graphic type LCD display with back light, USB host, for scan- |
| | ner or PC keyboard, KP-200 Plus keyboard display unit, KU-007 Plus programmable smart keyboard, |
| | Bluetooth module. |
| External labels holder | Additional |
| Dimensions | 109 mm (W) x 171 mm (H) x 209 mm (D) |
| Safety Regulations | FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC |